



## Market Stall Instructions

The Market Stall from Village Outreach provides a robust 2.5 m square covered area for your event. It requires at least 2 strong people to put it up and take it down.

Village Outreach can also supply tables and chairs if required.



## Introduction

The Market Stalls can be erected without any expert knowledge provided there are at least two fit adults available for lifting the roof and all those working on the erection do not rush and take reasonable care to avoid tripping over poles or banging their heads.

The each stall should be delivered with the following:

### Metalwork

- 4 Leg sections (square flat plates on the bottom – 1m long)
- 3 Bottom Rails (2.5 m long, no connections)
- 4 Uprights (1.2m long)
- 2 Front and Back rails
- 2 Side Rails
- 2 Roof Uprights (0.45m long)
- 1 Roof Apex
- 4 Roof members

### Canvas

- 1 Roof Sheet
- 3 Side Panels

Note: Village Outreach have two stalls, the frame of one has yellow paint on each piece whilst the other is marked with green. Try to keep the sections of each frame separate otherwise assembly can be very confusing.

## Step 1 - Feet

Put the four foot sections out as shown, note the rear ones have two sockets whilst the front ones have only one.



Rear foot



Front foot

## Step 2 – Bottom Rails



Now put the three bottom rails into place to form the 2.5m x 2.5m square with one side left open as shown opposite.

## Step 3 - Uprights

Now find the four uprights. They are straight bars with two sockets welded on the ends as show opposite.



They should be placed in each corner such that the two sockets outline the square.

Note the sockets which are now half way up each upright are not used.

#### Step 4 – Top Rails

Now put the front and back rails on (they are both the same). They are 2.5m long and have a socket in the middle.



These are followed by the two side rails which do not have the socket in the centre.

#### Step 5 – Roof Frame

Put a roof upright into the socket on the front and back rails



Now put the roof apex rail between the front and back rails.

The next stage is to put the four roof members between each corner and roof uprights as shown opposite.



Finally slot the additional roof members into place.

### **Step 6 – Covers**

The canvas roof is now put over the top of the stall and held down to the frame with the elastic cords. The sides are hung from the roof by hooks in the side panels.

